

What would threefold the life of radiant tubes do for your furnace productivity?

CASE STORY · CONTINUOUS STRIP ANNEALING · U- AND W-SHAPED RADIANT TUBES

The use of Kanthal APMT™ and Kanthal APM™ for radiant tubes in SSAB's annealing furnace has prolonged tube life and allowed for fewer furnace shutdowns, as well as the possibility to increase throughput by increasing tube temperature.

THE CHALLENGE

Short tube life hampers productivity

SSAB is a world-leading producer of high-strength and quenched steels. In Borlänge, Sweden, the company operates a continuous annealing line with a nitrogen-hydrogen atmosphere. The furnace is equipped with more than 200 W-shaped gas fired radiant tubes, each providing an output of 180 kW (615,000 BTU/h) giving 35 kW/m² (11,100 BTU/h/ft²), sufficient to maintain a maximum strip temperature of 880°C (1600°F). The maximum radiant tube temperature is 1050°C (1920°F).

In the most demanding zone of the furnace, the average life of the radiant tubes is between 1–4 years. Deformation of the burner leg is the main reason for the exchange of tubes. Three maintenance stops are planned each year, during which 30–50 tubes are replaced annually.

Prolonging the life of the radiant tubes would permit SSAB to increase the production time and improve throughput capacity. This could be achieved either by reducing the total number of maintenance stops, and/or by exchanging fewer tubes during each shutdown period.

THE SANDVIK SOLUTION

Short tube life hampers productivity

Sandvik radiant tubes made of Kanthal APMT or Kanthal APM offer long service life through excellent oxidation, carburization and high resistance to sagging. Both are advanced powder metallurgical, dispersion strengthened, ferritic iron-chromium-aluminum alloys that can be used at tube temperatures up to 1250°C (2280°F). Kanthal APMT is the premium alloy with the highest mechanical strength.

In December 2008 two hybrid W-tubes were installed in the highest temperature zone of the furnace, with the burner legs made from Kanthal APMT and the rest from a nickel-chromium alloy.



SSAB is a world leader in high strength steels.



The continuous annealing line at SSAB in Borlänge, Sweden.

THE RESULT

Fewer shutdowns thanks to threefold tube life

The Sandvik tubes were first inspected in November 2010, after 1.5 years of operation. Measurements showed sagging in the range of 0–2 mm (0–0.1 in). The reference cast tubes (iron-nickel-chromium and iron-nickel-chromium-niobium) had sagged 55–65 mm (2.2–2.6 in) during the same period.

At the inspection in April 2011, after 2.4 years in operation, sagging of the Kanthal APMT™ tubes was 0–5 mm (0–0.2 in). The last remaining reference tube had sagged 110 mm (4.3 in), and was replaced. The other references (four in total) were replaced after 1.5–2 years.

Extrapolation of the first inspection results indicates a threefold life potential of the W-tubes, and that the life limiting factor is the deformation of the second leg of the cast (nickel-chromium) tube section.

A second test period was started in November 2010, with the additional installation of two all Kanthal APM™ W-shaped tubes. It was determined that already Kanthal APM will considerably prolong the life of the W-tubes to the desired level.

Longer tube life allows for fewer furnace shutdowns. With the new alloys it is also possible to increase the tube temperature, and thereby increase the throughput capability of the furnace.



After 1.5 years of service in the hottest zone of a furnace, the W-tube with the burner leg made of Kanthal APMT showed a sagging of 0–2 mm (0–0.1 in).



The reference tubes, made of conventional cast material (iron-nickel-chromium), had sagged 55–65 mm (2.2–2.6 in). Two of the reference tubes were replaced already after 1.5 years.

Sandvik Group

The Sandvik Group is a global high technology enterprise with 47,000 employees in 130 countries. Sandvik's operations are concentrated on three core businesses: Sandvik Tooling, Sandvik Mining and Construction and Sandvik Materials Technology – areas in which the group holds leading global positions in selected niches.

Sandvik Materials Technology

Sandvik Materials Technology is a world-leading manufacturer of high value-added products in advanced stainless steels and special alloys, and of medical implants, steel belt-based systems and industrial heating solutions.

Kanthal is a Sandvik owned brand, under which world class heating technology products and solutions are offered. Sandvik, Kanthal, Kanthal APM and Kanthal APMT are trademarks owned by Sandvik Intellectual Property AB.

CHALLENGE YOUR EXPECTATIONS

Sandvik Materials Technology
Sandvik Heating Technology AB · Box 502 · 734 27 Hallstahammar, Sweden
Phone +46 220 210 00 · Fax +46 220 211 66
www.kanthal.com · www.smt.sandvik.com

